

**FULLY SYNTHETIC
ENGINE OIL 10W-50**

RAZER SERIES

NATO Stock No. 6850-32-087-9450

RAZER 4T RACING

LUPROMAX





Revolutionizing the Lubrication Industry through Heat Activated Technology

LUPROMAX[®]
Lubricates • Protects • Maximizes

LUPROMAX RAZER 4T RACING

NATO Stock No. 6850-32-087-9450

Fully Synthetic
Engine Oil 10W-50



DESCRIPTION

LUPROMAX Oil with Heat Activated Technology™ is specially developed to LUBricate, PROtect and MAXimize your engine performance.

LUPROMAX RAZER 4T RACING 10W-50 is engineered for maximum performance in 4-stroke engines, V-Twin engines and motorcycle transmissions. It is wet clutch compatible, shear stable and helps maintain proper oil pressure in elevated temperatures.

LUPROMAX RAZER 4T RACING 10W-50 with Heat Activated Technology™ contains LUPROMAX's proven synthetic technology with a high performance additive system to provide superb heat resistance and wear protection for ultimate performance and reliability.

LUPROMAX Oil is engineered to provide maximum power for your riding experience.

ADVANTAGES

- Provides outstanding heat resistance and highly effective protection from corrosion
- Reduces heat and promotes cooler operation
- Helps provide optimum acceleration and horsepower for highway cruising, high-speed and other performance application
- Excellent protection at peak engine RPM and power conditions
- Helps to extend the life of engines, transmission, and wet clutch primaries
- Excellent flow characteristics under extreme hot and cold operating conditions and during periods of intermittent use
- Reduces friction and engine noise, enhances shear stability for a quieter, smoother and enjoyable ride





LUPROMAX RAZER 4T RACING

NATO Stock No. 6850-32-087-9450

Fully Synthetic
Engine Oil 10W-50

APPLICATIONS

LUPROMAX RAZER 4T RACING 10W-50 is designed to optimize performance and protection for 4-stroke motorcycles where JASO MA are recommended.

- LUPROMAX RAZER 4T RACING 10W-50 is recommended for lubrication of 4-stroke motorcycle engines in high-performance motorcycles.
- LUPROMAX RAZER 4T RACING 10W-50 is recommended for use in early model air cooled V-Twin Harley-Davidson, Knucklehead, Panhead, Shovelhead and other big-bore motorcycles.
- LUPROMAX RAZER 4T RACING 10W-50 is suitable for extreme engine stress conditions, where conventional oil often may not perform

STORAGE

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Product should not be stored above 60°C, exposed to hot sun or freezing conditions.

TYPICAL PROPERTIES

Properties	Method	Specifications	Test Results
Appearance	Visual	Bright & Clear	B & C
Color	D 1500	Max 3.5	< 3.5
Density @15°C	kg/l	ASTM D4052	Report
Density @30°C	kg/l	ASTM D4052	Report
Kinematic Viscosity @40°C	cSt	ASTM D445	Report
Kinematic Viscosity @100°C	cSt	ASTM D445	16.3 - 21.9
Viscosity Index		ASTM D2270	Min 155
TBN	mgKOH/g	ASTM D2896	Min 7.0
Flash Point	°C	ASTM D92	Min 205
Pour Point	°C	ASTM D97	Max -24
CCS	cP	ASTM D5293	5883

HEALTH, SAFETY & ENVIRONMENT

Health and Safety

LUPROMAX RAZER is unlikely to present any significant health or safety hazard when used properly in the recommended application provided in the Material Safety Data Sheet (MSDS) are followed.

Avoid contact with skin. Use impervious gloves with used oil. After skin contact, wash immediately with soap and water. Guidance on Health and Safety is available on the appropriate Material Safety Data Sheet, which can be obtained upon request through your sales contract office, or via the internet.

Protect the Environment

Take used oil to an authorized collection point. Do not discharge into drains, soil or water.

AVAILABLE PACKAGING

20 liters pail/ 200 liters drum

LUPROMAX RAZER 4T 10W-50 exceeds the requirements of:

API SN/JASO MA



Revolutionizing the Lubrication Industry through Heat Activated Technology

LUPROMAX[®]

For more information about Lupromax products, please contact your local distributor or Magna offices:

Distributed by:



Headquarters & Far East Office:
Magna International Pte Ltd
10H Enterprise Road
Singapore 629834
Tel (65) 6788 1228
Fax (65) 6785 1497
Email info@magnachem.com.sg
Website <http://www.lupromax.com>

North America Office:
1450 Government Rd West
Kirkland Lake Ontario P2N 2E9
Canada
Tel 1.416 479 9151
Fax 1.888 317 1993
Email magna@vapro.com

Australia Office:
6/23-25 Bunney Rd,
Oakleigh South VIC 3167, Australia
Tel (61) 3 9558 2980
Fax (61) 3 9558 3430
Email info@lupromax.com.au
Website <http://www.lupromax.com.au>



ISO 9001



ISO 14001



This data sheet and the information it contains is believed to be accurate as the data of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version on this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken for any damage or injury resulting from abnormal use of material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.